

## LED 2<sup>nd</sup> GEN TROFFER SERIES

### FEATURES

- Environmentally friendly; free of mercury, IR, and UV emissions.
- Smooth and consistent lighting distribution
- Ideal for retrofitting recessed fluorescent troffer fixtures
- Dimmable ( 1-10V - Available on selected dimmers- see compatibility chart)
- ETL & DLC listed
- Suitable for damp locations
- Five-year warranty



### APPLICATION

Commercial, Retail, Offices



## COMING SOON!

### Technical Specification

Part No.	Watt. (W)	Lumens (lm)	CCT(K)	Voltage	Size (inch)	Weight (lb)	CRI(Ra)
RLT-CB-22/27W40K	27	2916	4000	AC100-277V 60Hz	L23.82**W23.82**H3.94"	9.70	80
RLT-CB-22/27W50K	27	2916	5000	AC100-277V 60Hz	L23.82**W23.82**H3.94"	9.70	80
RLT-CB-22/42W40K	42	4536	4000	AC100-277V 60Hz	L23.82**W23.82**H3.94"	9.70	80
RLT-CB-22/42W50K	42	4536	5000	AC100-277V 60Hz	L23.82**W23.82**H3.94"	9.70	80
RLT-CB-24/42W40K	42	4536	4000	AC100-277V 60Hz	L47.72**W23.82**H3.94"	18.96	80
RLT-CB-24/42W50K	42	4536	5000	AC100-277V 60Hz	L47.72**W23.82**H3.94"	18.96	80
RLT-CB-24/65W40K	65	7020	4000	AC100-277V 60Hz	L47.72**W23.82**H3.94"	18.96	80
RLT-CB-24/65W50K	65	7020	5000	AC100-277V 60Hz	L47.72**W23.82**H3.94"	18.96	80

Dimmable	Yes(1-10V)
Beam Angle	80°
PF	0.9
Working Temperature (C°)	-20~ +40 (C°)
Lifetime (H)	50000
Suitable Locations	Damp

